ELSEVIER

Engineering Geology 57 (2000) 239

ENGINEERING GEOLOGY

www.elsevier.nl/locate/enggeo

Author Index Volume 57

Amelio, M., see Ferrucci, F. 53
Bolton, A.J.
Some measurements of permeability and effective stress on a heterogeneous soil mixture: implications for recovery of inelastic strains 95
Cetin, H.
An experimental study of soil memory and preconsolidation adjacent to an active tectonic structure: the Meers fault, Oklahoma, USA 169
Darban, A.K., Foriero, A. and Yong, R.N.
Concentration effects of EDTA and chloride on the retention of trace metals in clays 81
Dobrev, N.D. and Košt'ák, B.
Monitoring tectonic movements in the Simitli Graben, SW Bulgaria 179
Donnelly, L.J. and McCann, D.M.
The location of abandoned mine workings using thermal techniques 39
El-Mahdy, O.R., see Moufti, M.R. 155
Erdogan, M.
Measurement of polished rock surface brightness by image analysis method 65
Ferrucci, F., Amelio, M., Sorriso-Valvo, M. and Tansi, C.
Seismic prospecting of a slope affected by deep-seated gravitational slope deformation: the Lago Sackung, Calabria, Italy 53
Foriero, A., see Darban, A.K. 81
Gökçeoğlu, C., Ulusay, R. and Sönmez, H.
Factors affecting the durability of selected weak and clay-bearing rocks from Turkey, with particular emphasis on the influence of the number of drying and wetting cycles 215
Hatheway, A.W. and Kanaori, Y.
Annual status of the profession: 1999, Encompassing hydrogeology, environmental geology and the applied geosciences 133
Inci, G., see Yesiller, N. 105
Jethwa, J.L., see Jhanwar, J.C. 13
Jhanwar, J.C., Jethwa, J.L. and Reddy, A.H.
Influence of air-deck blasting on fragmentation in jointed rocks in an open-pit manganese mine 13
Jiao, J.J., see Zhang, J. 31
Kanaori, Y., see Hatheway, A.W. 133
Karagüzel, R. and Kiliç, R.
The effect of the alteration degree of ophiolitic melange on permeability and grouting 1
Kiliç, R., see Karagüzel, R. 1
Košt'ák, B., see Dobrev, N.D. 179
McCann, D.M., see Donnelly, L.J. 39
Miller, C.J., see Yesiller, N. 105
Mohamed, A.M.O.
The role of clay minerals in marly soils on its stability 193
Moufti, M.R., Sabtan, A.A., El-Mahdy, O.R. and Shehata, W.M.
Assessment of the industrial utilization of scoria materials in central Harrat Rahat, Saudi Arabia 155
Ravikumar, N., see Sarma, L.P. 123
Reddy, A.H., see Jhanwar, J.C. 13
Reznik, Y.M.
Engineering approach to interpretation of oedometer tests performed on collapsible soils 205
Sabtan, A.A., see Moufti, M.R. 155
Sarma, L.P. and Ravikumar, N.
Q-factor by spectral ratio technique for strata evaluations 123
Shehata, W.M., see Moufti, M.R. 155
Sijing, W., see Siqing, Q. 163
Siqing, Q. and Sijing, W.
A homomorphic model for identifying abrupt abnormalities of landslide forerunners 163
Sönmez, H., see Gökçeoğlu, C. 215
Sorriso-Valvo, M., see Ferrucci, F. 53
Sun, Y., see Tan, C. 73
Tan, C., Sun, Y. and Wang, R.
Present day activity of the Shenzhen fault zone and its impact on the safety of a planned diversion tunnel in Shenzhen, China 73
Tansi, C., see Ferrucci, F. 53
Ulusay, R., see Gökçeoğlu, C. 215
Wang, R., see Tan, C. 73
Yaldo, K., see Yesiller, N. 105
Yang, J., see Zhang, J. 31
Yesiller, N., Miller, C.J., Inci, G. and Yaldo, K.
Desiccation and cracking behavior of three compacted landfill liner soils 105
Yong, R.N., see Darban, A.K. 81
Zhang, J., Jiao, J.J. and Yang, J.
In situ rainfall infiltration studies at a hillside in Hubei Province, China 31

0013-7952/00/$ – see front matter © 2000 Elsevier Science B.V. All rights reserved.
PII: S0013-7952(00)00045-4

ELSEVIER

Engineering Geology 57 (2000) 241–242

ENGINEERING GEOLOGY

www.elsevier.nl/locate/enggeo

Subject Index Volume 57

Abnormality, 163
Active fault, 169
Air-deck, 13
Alteration, 1
Aseismic, 169

Basalt, 123
Blasting, 13
Brightness, 65

Calabria, 53
Case study, 163
Cement additive, 155
Chloride, 81
Clay, 81, 193
Clay-bearing rocks, 215
Coal, 39
Collapse potential, 205
Collapsible soils, 205
Confidence interval, 163
Consolidation, 95
Cracking, 105

Dam site, 1
Deformation modulus, 205
Desiccation, 105
Displacement, 179
Double oedometer tests, 205

Earthquakes, 169
EDTA, 81
Effective stress, 95, 169
Extensometers, 179

Fault creep, 169
Fault displacement rate, 73
Faults, 179
Fragmentation, 13

Geohazard, 39
Grinding, 65
Groundwater, 31
Grouting, 1

Heat insulation, 155
Homomorphic model, 163

Image analysis, 65
India, 123
Infiltration test, 31
In situ stress measurement, 73

Jointed rock, 13

Landfill, 105
Landslide, 163
Landslides, 31
Lightweight aggregate, 155
Liner, 105

Marble, 65
Marl, 193
Mass-movement, 53
Measurement, 65
Meers fault, 169
Minegas, 39
Mining, 39
Monitoring, 179

Oklahoma, 169
Open pit, 13
Ophiolitic melange, 1
Overconsolidation, 169
Overconsolidation ratio, 169

Permeability, 1, 95
Pore fluid pressure, 95
Pozzolanic activity, 155
Preconsolidation, 169
Present tectonic activity, 73
Present tectonic stress state, 73

Q-factor, 123

Regression analysis, 215
Rock Quality Designation, 123

Saudi Arabia, 155
Scoria, 155
Seismic, 169
Shafts, 39
Shallow seismic reflection analysis, 53
Single oedometer tests, 205

0013-7952/00/$ – see front matter © 2000 Elsevier Science B.V. All rights reserved.
PII: S0013-7952(00)00046-6

Slake durability, 215
Slope failure, 31
Soil constituents, 81
Soil fabric, 169
Soil memory, 169
Soil retention, 81
Soil stabilization, 193
Soil suction, 31
Southwest Bulgaria, 179
Structural geology, 53
Suction, 105

Thermal techniques, 39
Thermodynamic stability, 193
Three-dimensional tectonic stress field, 73
Trace metals, 81

Uniaxial compressive strength, 215
Unsaturated flow, 31